



US008151797B2

(12) **United States Patent**
Chang

(10) **Patent No.:** **US 8,151,797 B2**
(45) **Date of Patent:** **Apr. 10, 2012**

(54) **RESPIRATION MASK ASSEMBLY**
(75) Inventor: **Eric Chang**, Taichung Hsein (TW)
(73) Assignee: **Hsiner Company, Ltd.**, Taichung Hsien (TW)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 772 days.
(21) Appl. No.: **12/261,409**
(22) Filed: **Oct. 30, 2008**

6,532,961	B1 *	3/2003	Kwok et al.	128/206.21
6,557,556	B2 *	5/2003	Kwok et al.	128/207.11
6,691,708	B2 *	2/2004	Kwok et al.	128/207.11
7,059,326	B2 *	6/2006	Heidmann et al.	128/207.11
7,234,773	B2 *	6/2007	Rafferty et al.	297/284.4
7,610,916	B2 *	11/2009	Kwok et al.	128/207.11
2003/0062048	A1 *	4/2003	Gradon et al.	128/207.11
2003/0075180	A1 *	4/2003	Raje et al.	128/206.24
2003/0089373	A1 *	5/2003	Gradon et al.	128/206.27
2004/0182398	A1 *	9/2004	Sprinkle et al.	128/207.13
2004/0255949	A1 *	12/2004	Lang et al.	128/206.21
2005/0039753	A1 *	2/2005	Schumacher	128/206.27
2005/0197605	A1 *	9/2005	Bonutti et al.	602/5
2006/0191538	A1 *	8/2006	Heidmann et al.	128/207.11
2008/0135050	A1 *	6/2008	Hitchcock et al.	128/207.11
2010/0071700	A2 *	3/2010	Hitchcock et al.	128/207.11
2011/0186045	A1 *	8/2011	Erickson	128/201.23

* cited by examiner

(65) **Prior Publication Data**
US 2010/0108069 A1 May 6, 2010


Primary Examiner — Stephen Crow
(74) *Attorney, Agent, or Firm* — Jeffrey D. Myers; Peacock Myers, P.C.

(51) **Int. Cl.**
A61M 16/06 (2006.01)
(52) **U.S. Cl.** **128/207.11**; 128/260.24
(58) **Field of Classification Search** 128/206.11–206.29, 207.11
See application file for complete search history.

(57) **ABSTRACT**
A respiration mask assembly including: a mask body having a front part that defines a front opening adapted to communicate fluidly with a gas supply, and a rear part that defines a rear opening opposite to the front opening in a horizontal direction; a forehead support beam extending outwardly from and pivoted to the front part of the mask body so as to rotate relative to the mask body about a first axis transverse to the horizontal direction; and a worm pivoted to the front part of the mask body. The forehead support beam has a toothed pivot end engaging the worm such that rotation of the worm about a second axis transverse to the first axis results in rotation of the forehead support beam about the first axis.

(56) **References Cited**
U.S. PATENT DOCUMENTS
2,747,464 A * 5/1956 Bowerman 359/382
4,034,426 A * 7/1977 Hardwick et al. 4/564.1
4,663,931 A * 5/1987 Schiffers et al. 60/784
4,944,210 A * 7/1990 Flock et al. 89/1.818
5,906,199 A * 5/1999 Budzinski 128/201.11
6,062,148 A * 5/2000 Hodge et al. 108/147
6,119,693 A * 9/2000 Kwok et al. 128/207.11
6,374,826 B1 * 4/2002 Gunaratnam et al. ... 128/206.27

5 Claims, 5 Drawing Sheets






FIG. 1
PRIOR ART




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1

RESPIRATION MASK ASSEMBLYCROSS-REFERENCE TO RELATED
APPLICATIONS

Not Applicable.

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable.

INCORPORATION BY REFERENCE OF
MATERIAL SUBMITTED ON A COMPACT DISC

Not Applicable.

COPYRIGHTED MATERIAL

Not Applicable.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to a respiration mask assembly, more particularly to a respiration mask assembly including a mask body and a forehead support beam pivoted to the mask body.

2. Description of the Related Art

FIG. 1 illustrates a conventional pressure support respiration mask assembly that includes a mask body **101** defining a front opening **102** for communicating fluidly with a gas supply (not shown) through a conduit **2**, a forehead support beam **103** extending from the mask body **101** and formed with a forehead-abutting member **104** for abutting against the forehead of the wearer, a pair of upper straps **105** connected to the forehead support beam **103**, and a pair of lower straps **106** connected to the mask body **101**.

The conventional pressure support respiration mask assembly is disadvantageous in that the forehead support beam **103** is integrally formed with the mask body **101**, which cannot be adjusted relative to the mask body **101**, which can result in wearer discomfort due to a tight fastening of one of the pairs of the upper and lower straps **105**, **106** when the profile from the forehead support beam **103** to the mask body **101** does not fit the facial profile of the wearer.

SUMMARY OF THE INVENTION

Therefore, the object of the present invention is to provide a respiration mask assembly that can overcome the aforesaid drawback associated with the prior art.

According to the present invention, there is provided a respiration mask assembly that comprises: a mask body having a front part that defines a front opening adapted to communicate fluidly with a gas supply, and a rear part that defines a rear opening opposite to the front opening in a horizontal direction; a forehead support beam extending outwardly from and pivoted to the front part of the mask body so as to rotate relative to the mask body about a first axis transverse to the horizontal direction; and a worm pivoted to the front part of the mask body. The forehead support beam has a toothed pivot end engaging the worm such that rotation of the worm

2

about a second axis transverse to the first axis results in rotation of the forehead support beam about the first axis.

BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the present invention will become apparent in the following detailed description of the preferred embodiment with reference to the accompanying drawings, of which:

FIG. 1 is a schematic partly sectional view of a conventional pressure support respiration mask assembly;

FIG. 2 is a cutaway perspective view of the preferred embodiment of a pressure support respiration mask assembly according to the present invention;

FIG. 3 is a fragmentary schematic view of the preferred embodiment;

FIG. 4 is an exploded perspective view of the preferred embodiment; and

FIG. 5 is a sectional view of the preferred embodiment.

DETAILED DESCRIPTION OF THE PREFERRED
EMBODIMENT

Referring to FIGS. 2-5, the preferred embodiment of a pressure support respiration mask assembly according to the present invention is shown to include: a mask body **10** having a front part **11** that defines a front opening **163** adapted to communicate fluidly with a gas supply (not shown) through a conduit **40** (see FIG. 5), and a rear part **17** that defines a rear opening **15** opposite to the front opening **163** in a horizontal direction (Y); and a forehead support beam **23** extending outwardly from and pivoted to the front part **11** of the mask body **10** so as to rotate relative to the mask body **10** about a first axis (X) transverse to the horizontal direction (Y). An annular protrusion **162** protrudes outwardly from a periphery of the front opening **163** of the front part **11** of the mask body **10** for connecting with the conduit **40**.

In this embodiment, a worm **30** is pivoted to the front part **11** of the mask body **10**. The forehead support beam **23** has a toothed pivot end **231** engaging the worm **30** such that rotation of the worm **30** about a second axis (Z) transverse to the first axis (X) results in rotation of the forehead support beam **23** about the first axis (X). The toothed pivot end **231** of the forehead support beam **23** has an arcuate end face formed with a plurality of teeth **24**.

In this embodiment, the front part **11** of the mask body **10** is formed with a mounting recess **16**. The worm **30** is received in the mounting recess **16**. The mounting recess **16** is defined by a recess-defining wall **16'** that has a top open end **166'**, a front open end **165'**, and a rear closed end **164** (see FIG. 2) opposite to the front open end **165'** in the horizontal direction (Y). The top open end **166'** defines a top opening **166** of the mounting recess **16** for extension of the toothed pivot end **231** of the forehead support beam **23** therethrough and into the mounting recess **16**. The front open end **165'** defines a front opening **165** of the mounting recess **16**. The front part **11** of the mask body **10** is provided with a supporting plate **13** that is fitted into the front open end **165'** of the recess-defining wall **16'** to cover the front opening **165** of the mounting recess **16**. The worm **30** has first and second pivot ends **31**, **32** that are pivoted to the rear closed end **164** of the recess-defining wall **16'** and the supporting plate **13**, respectively, and that cooperatively define the second axis (Z). The worm **30** further has a threaded portion **33** extending between the first and second pivot ends **31**, **32** and engaging the teeth **24** of the toothed pivot end **231** of the forehead support beam **23** so as to permit adjustment of the angular position of the forehead support

3

beam **23** relative to the mask body **10**. The supporting plate **13** is formed with a through-hole **131** for extension of the second pivot end **32** of the worm **30** therethrough. An operating knob **34** is disposed outwardly and frontwardly of the mounting recess **16**, and is connected securely to the second pivot end **32** of the worm **30** for facilitating the operation of driving rotation of the worm **30** about the second axis (Z).

The front part **11** of the mask body **10** is further provided with a pivot shaft **14**, and is further formed with two opposite pivot ears **18** protruding outwardly of the mounting recess **16** from the top open end **166'** of the recess-defining wall **16'**. The pivot shaft **14** defines the first axis (X), and has two opposite ends secured to the pivot ears **18**, respectively. The toothed pivot end **231** of the forehead support beam **23** is disposed between the pivot ears **18** and is pivoted to the pivot shaft **14** which extends through the toothed pivot end **231** of the forehead support beam **23**.

In this embodiment, a hollow cushioning member **12** is connected securely to and flares rearwardly from a periphery of the rear part **17** of the mask body **10**, and has a constricted rear end that defines a constricted rear opening **121** for extension of the nose of the wearer therethrough and into the mask body **10**.

In this embodiment, an elastic forehead-abutting member **26** is spaced apart from the mask body **10**, and is adapted to abut against the forehead of the wearer. The forehead support beam **23** further has a connecting end **232** that is provided with an end plate **22**. The forehead-abutting member **26** is mounted detachably on the end plate **22**. The end plate **22** is formed with two fastening holes **25** for fastening of a pair of straps **100** to the end plate **22**. The mask body **10** is further formed with two loop-shaped ears **19** for fastening of another pair of straps **100** to the mask body **10**.

By pivoting the forehead support beam **23** to the front part **11** of the mask body **10** of the respiration mask assembly of this invention, the angular position of the forehead support beam **23** relative to the mask body **10** can be adjusted, thereby eliminating the aforesaid drawback associated with the prior art.

While the present invention has been described in connection with what is considered the most practical and preferred embodiment, it is understood that this invention is not limited to the disclosed embodiment but is intended to cover various arrangements included within the spirit and scope of the broadest interpretation so as to encompass all such modifications and equivalent arrangements.

What is claimed is:

1. A respiration mask assembly comprising:

a mask body having a front part that defines a front opening adapted to communicate fluidly with a gas supply, and a rear part that defines a rear opening opposite to said front opening in a horizontal direction;

a forehead support beam extending outwardly from and pivoted to said front part of said mask body so as to rotate

4

relative to said mask body about a first axis transverse to said horizontal direction; and

a worm pivoted to said front part of said mask body, said forehead support beam having a toothed pivot end engaging said worm such that rotation of said worm about a second axis transverse to said first axis results in rotation of said forehead support beam about said first axis; and

wherein said front part of said mask body is formed with a mounting recess, said worm being received in said mounting recess; and

wherein said mounting recess is defined by a recess-defining wall that has a top open end, a front open end, and a rear closed end opposite to said front open end in the horizontal direction, said top open end defining a top opening of said mounting recess for extension of said toothed pivot end of said forehead support beam therethrough and into said mounting recess, said front open end defining a front opening of said mounting recess, said front part of said mask body being provided with a supporting plate that is fitted into said front open end of said recess-defining wall to cover said front opening of said mounting recess, said worm having first and second pivot ends that are pivoted to said rear closed end of said recess-defining wall and said supporting plate, respectively, and that cooperatively define said second axis.

2. The respiration mask assembly as claimed in claim 1, wherein said front part of said mask body is further provided with a pivot shaft, and is further formed with two opposite pivot ears protruding outwardly of said mounting recess from said top open end of said recess-defining wall, said pivot shaft defining said first axis and having two opposite ends secured to said pivot ears, respectively, said toothed pivot end of said forehead support beam being disposed between said pivot ears and being pivoted to said pivot shaft.

3. The respiration mask assembly as claimed in claim 1, further comprising an operating knob disposed outwardly and frontwardly of said mounting recess and connected securely to said second pivot end of said worm.

4. The respiration mask assembly as claimed in claim 1, further comprising a hollow cushioning member flaring rearwardly from a periphery of said rear part of said mask body and having a constricted rear end that defines a constricted rear opening for extension of the nose of the wearer therethrough and into said mask body.

5. The respiration mask assembly as claimed in claim 1, further comprising a forehead-abutting member spaced apart from said mask body and adapted to abut against the forehead of the wearer, said forehead support beam further having a connecting end that is provided with an end plate, said forehead-abutting member being mounted detachably on said end plate.

* * * * *